

Type

Latex-free and odourless water-borne furniture paint. INTO is safe, eco-friendly and easy to use. The reason INTO is ecological are the renewable natural oils that work as the binder. It does not contain any plastic agents.

Intended use

For interior wooden surfaces, chipboards and fibreboards. Furniture, doors, battens, window panes, cupboards etc.

Technical qualities

Density approx. 1.3 kg/L.

Gloss grade: Semi-matt and Semi-glossy.

Emission class M1 in building materials.

Wet abrasion resistance class SFS 3755; over 5000 brush strokes.

Washable.

Does not contain any VOC.

Non-flammable

Colours

White and colours from Uula interior and traditional colour chart that are made to the A & C tinting bases. Wide range of colours to choose from; Can be tinted according to most common colour charts.

Application & conditions

Ordinary paint brush or mohair roller.

The surface to be painted must be dry, the relative air humidity below 80 % and the temperature at least +10°C.

Drying time

Tack-free in approx. 30 minutes. A new coat of paint can be applied after 2 hours. (+20°C and the relative air humidity below 80%)

Coverage

Approx 7 m²/L depending on the coarseness and porosity of the surface.

Thinner

Water

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Container sizes

0.9 L, 2.7 L and 9 L

Storage and disposal

Keep in a cool and dry place. Do not allow to freeze!

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point.



Painting instructions:

Unpainted surface

Wash dirty surfaces with Uula Washing Agent following the instructions. Allow to dry thoroughly before painting. Level all cracks and holes in the surface with putty if necessary. Prime new wooden surfaces with INTO Primer. Apply one or two coats of INTO Furniture Paint. Thin with water if necessary.

Old painted surface

Remove peeling and flaking old paint. Sand a glossy or hard surface with a sandpaper. Wash dirty surfaces with Uula Paint Washing Agent following the instructions. Allow to dry thoroughly before painting. Level all cracks and holes in the surface with putty if necessary. Apply one or two coats of INTO Furniture Paint. Thin with water if necessary.

Further treatment of the surface

Be really careful with all painted surfaces during the first month. Clean the surface only with soft rags and sponges that do not scratch the surface. Use only neutral washing agents. Rinse the surfaces carefully.

Points to note

- *Stir well before use during painting
- *Reserve enough paint for a large surface in order to avoid potential colour variations in different batches.
- *Do a test paint to ensure the colour is correct.
- *Always choose the colour in the same lighting and space where the painting will be done in.
- *In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.